



SPECIFICATIONS WITHOUT CIRCUIT

MODEL NO:	DMT-1206	DMT-1206-3.3
RATED VOLTAGE DC (V):	6	3.3
OPERATING VOLTAGE DC (V):	4~8	2~5
CURRENT(mA):	MAX. 40	MAX. 40
SOUND OUTPUT AT 10CM(dB):	MIN. 85	MIN. 85
COIL RESISTANCE:	50	50
RESONANT FREQ. (Hz):	2,200	2,200
TEMPERATURE RANGE(°C):	-40 TO +85	-40 TO +85
WEIGHT(g):	2	2
DIMENSIONS(mm):	Ø12X9.5H.	Ø12X9.5H

NOTE:

1. ALL DIMS ARE GIVEN IN MM.
2. PC PINS ARE ALSO AVAILABLE IN 3.3MM OR 2.92MM LENGTHS.
3. FLOW SOLDERABLE AND WASHABLE.
4. DMT-1206 MODEL SHOWN

PROJECTION		Research Develop Innovate RDI, Inc. 400 Columbus Avenue Valhalla, NY 10595	
	SCALE	TITLE	
	NONE	AUDIO ALERT	
TOLERANCE EXCEPT AS NOTED	DR. JOEY	DATE 3/14/02	REF. P/N: DMT-1206 SERIES
DEC. INCHES N/A	CK. SL	PRE-BZ	DRAWING NO. 0654 SIZE A REV. E
DEC. MILLIMETERS ±0.3	THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.		
ANG. N/A			

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY
04-444	6/18/04	E	DELETED DMT-1206-S, SEE DWG BZ-1946-A	BM	JY
04-316	5/11/04	D	P/N DMT-1206 SERIES WAS DMT-12 SERIES. REMOVED DMT-1212 SERIES	BM	JY
03-667	9/19/03	C	UPDATED TO STANDARDS	NL	JY
03-375	5/19/03	B	ADDED DIM: (2)-Ø0.6±0.1	BM	JY
02-224	6/10/02	A	ADDED MODLE DMT-1206-3.3	BM	JY